

Uwaga:

Rozpatrywać z ark. 1 nr arch. 1- 0465

14.	[65 - ¹¹⁵⁰ 950 @	6	st 3s	40,4	
13.	Bł. 8 × 90 × 250 ³⁵⁰ @	4	- -	4,4	
12.	Bł. 12 × φ 70	2	- -	0,6	
11.	Bł. 10 × 124 × 590	1	- -	4,2	
10.	Bł. 8 × 50 × 585	6	- -	11,0	
9.	Bł. 8 × 50 × 590	6	- -	9,2	
8.	Bł. 8 × 84 × 92	2	- -	1,0	
7.	Bł. 8 × 92 × 270	2	- -	3,1	
6.	Bł. 8 × 50 × 1410	4	- -	14,2	
5.	Bł. 8 × 90 × 1452	4	- -	23,8	
4.	Bł. 8 × 50 × 523	4	- -	6,5	
3.	Bł. 8 × 92 × 400	2	- -	4,6	
2.	Bł. 8 × ¹¹⁵⁰ 950 @ × 1371	2	- -	163,6	
1.	Bł. 8 × 1410 × 1460	2	st 3s	192,2	

@ × 3 28. 11. 83r.

kopiuwano 11.83r.

E. Gerniak 11.83r. F. Gierb

inż. A. Drożdżowski 11.83r.

mgr inż. J. Noworyta 11.83r.

Zsunia dwukierunkowa
z przestawiakiem. KS 36
KS 42

Kosz ark. 2

485,-


04 12 01 05 00



4-2323

Uwaga:

Rozpatrywać z ark. 1 nr. arch. 1-0463

20	[140, L=360]	2	st 35		
19.	Podkładka spr. 16,3	10	wg normy	0,08	
18.	Nakrętka M16-5-II	10	-II-	0,33	
17.	Śruba M16×40-5.8 II	10	wg normy	0,89	
16.	L 60×60×8-920	4	st 35	13,0	
15.	L 60×60×8- 430 1330 @	4	-II-	16,0	
14.	[140- 440 1346 @	1	-II-	18,2	
13.	[140-1720 +400	2	-II-	55,0	
12.	[140- 1143 ^{1x lewy} _{1x prawy}	2	-II-	36,5	L=1460
11.	Bl. 8×450×450	4	-II-	38,0	
10.	Bl. 8×60×110	6	-II-	2,5	
9.	Bl. 8×60×700	6	-II-	15,8	
8.	Bl. 8×60×450	18	-II-	30,5	
7.	Bl. 8×60×426	12	-II-	19,2	
6.	Bl. 8×60× 430 1330 @	4	-II-	17,0	
5.	Bl. 8×60× 430 1330 @	2	-II-	8,5	
4.	Bl. 8×183× 430 1330 @	2	-II-	26,0	
3.	Bl. 8× ¹³³⁰ 430 ×1565 @	1	-II-	101,0	
2.	Bl. 8× ¹³³⁰ 430 ×1565 @	1	-II-	101,0	
1.	Bl. 8×608×1646	2	st 35	88,30	

@ x 7 28. 11. 83r. 

kopiowano 11. 83r.
 E. Gerniak 11. 83r. 
 inż. A. Drożdżowski 11. 83r.
 inż. J. Noworyta 11. 83r. 

Zsuwnia dwukierunkowa
 z przestawiakiem KS36 i KSK2

Zsuwnia III ark.2 5830-

04 . 12 01 | 03 | 00

4-2322